



High Efficiency

LED Street Light Modules

FEATURES:

- Constant Current Output
- Open Circuit Output and Short Circuit Protection
- Each Group has Independent current detection
- HYP190x series providing 99% conversion efficiency

- ✓ LED Road Light Equipment
- ✓ LED Solar Power Road Light, Landscape Light, Atmosphere Light
- ✓ High Power Spot Light for Outdoor Billboard and Micro-Projector Equipment
- ✓ Light Box and Panel Backlight Source
- ✓ Other High Power Lighting Equipment



Desc.	HYP190x series	HYP1901	HYP2105
Input Voltage	24V or 48V	24V	10.5V~18V
Input Current (Max)	2A	4A	3A
Efficiency (Max)	96%	99%	94%
Output Voltage (Typical)	22V~44V	22V	13.2V~32V
Output Current (Typical)	350mA~700mA	4.2A	900mA~1400mA
Output Power (Max)	30W~100W	100W	30W(Max)
Operating Temperature Range	-20 ⁰ C~ +85 ⁰ C	-20 ⁰ C~ +85 ⁰ C	-20 ⁰ C~ +85 ⁰ C
Droupt Voltage (Vin-Vout) (Mini mun)	0.2V	0.2V	—
Other Fuction	—	—	Voltage Reverse Protection



HAWYANG SEMICONDUCTOR CORP. 浩陽半導體股份有限公司

Taiwan 6F., No. 96, Minchuan Rd., Xindian, Taipei County, Taiwan Tel: 886-2-2219-0903 Fax: 886-2-2219-3189

Shenzhen Room 12B-9, Zheng Quan Building, No.5020, Bin He Avenue, Fu Tian District, Shen Zhen City Tel: (0755)89807897 Fax: (0755)82990700

E-mail: power4led@hawyang-semi.com www.hawyang-semi.com / www.power4led.com